R

TX-5353SW330C36F17-03H952770

PRODUCT SPECIFICATION (R&D version)

Features:


H53WV

tput.

E	LED	5A.		,	
Р			FVRVO	,	
H			IPI		
N UV.		· 4		- 100	

Chip Material

P N . T -5353S 330C36F17-03H952770 S N . R&D P 1 3



Absolute Maximum Ratings

Parameter	Symbol	Ratings	Unit
F C	IF	6	Α
R V	V _R	N William Comment	V
	S	300	
P D	P _D	300	
NS.	S+	330	
J	T S	135	
3		135	
C T (C)	Т	85	
S T	Т	-30 +70	
O T	T	-30 +85	A Latid

Notes:

1.S . . .

2.T

3.P ESD:

STATIC SHIELD E LED. I

- LED. A ,

P N . T -5353S 330C36F17-03H952770 S N . R&D P 3 3

. . V :1.0

Electrical Optical Characteristics (Tc=25°C)

Parameter	Symbol	Condition	Emitting color	Min.	Тур.	Max.	Units
L F			Red Control		15000		
		HH Hallian		./8	22000		
5 V	V	Guard	S	47	49	51	
F V	V			47	49	51	V
СС	ССТ	- I =5A	S		2700		12
T	ССТ		IRT		7000		K
			S		115		D
V A 50 IV	2 1/2			A Tilled	115		D
R C	I _R			High cities			A
T R	В	Me To Pic	S	ÓL.	0.12		K/
J C	R _{J-C}	I =5A	Litang itou		0.12	14 M	State of N
C D I	A THE BOTH] I=5A	S		95	A This land	
C R I	Handing R	.61			95	RELEGIE	

Notes:

1.L CIE

- .

2. 1/2 -

3.L : 15%. 4.F : 3%.

5.R : 2.

PN.	T -5353S 330C36F17-03H952770	S N.	R&D	Р	4 3
-----	------------------------------	------	-----	---	-----

. . V :1.0